



## MINIMUM MELTING TIME-CURRENT CHARACTERISTIC CURVES

### POSITROL® FUSE LINKS—S&C “T” SPEED

**BASIS**—These fuse links are tested in accordance with the procedures described in ANSI Standard C37.41-1981, to comply with ANSI Standard C37.42-1981. As required by these standards, the minimum melting current is not less than 200% of fuse-link ampere rating, and the minimum melting curves are based on tests starting with the fuse link at an ambient temperature of 25°C and no initial load.

**CONSTRUCTION**—Fusible elements for fuse links rated 6T through 100T amperes are silver-copper eutectic, helically coiled; fusible elements for fuse links rated 140T and 200T amperes are cast tin. All are of solderless construction.

**TOLERANCES**—Curves are plotted to maximum test points. Maximum variations within the coordinating range (melting times less than 10 seconds) expressed in current values are:

- Plus 10% for fuse links rated 6T through 100T amperes;
- Plus 20% for fuse links rated 140T and 200T amperes.

**APPLICATION**—Like all high-voltage fuses, these fuse links are intended to accommodate overloads, not to interrupt them. Accordingly, they feature fusible elements which are designed with a minimum melting current of 200% of the fuse-link ampere rating (for fuse links rated 100T amperes or less) or 220% of the fuse-link ampere rating (for fuse links rated over 100T amperes). As a result, these fuse links have considerable peak-load capabilities; however, they should never be exposed to loading in excess of the peak-load capabilities listed in S&C Data Bulletin 350-190.

Since fuse links having silver-copper eutectic element construction are not subject to damage by aging or transient overcurrents, it is unnecessary to replace unblown fuse links of such construction in single-phase or three-phase installations when one or more fuse

links have blown. However, it is advisable to replace unblown cast-tin element fuse links under the same conditions, since they may be damaged by transient overcurrents.

**COORDINATION**—Any preloading reduces melting time. While this phenomenon is especially pronounced in fuse linkss having minimum melting currents appreciably less than 200% of rating, the effect of preloading (as described in S&C Data Bulletin 350-195) must nonetheless be determined for the fuse links represented by these curves and adjustments to these curves must be made:

1. When close coordination is required;
2. When automatic circuit reclosers or three-shot cutouts are involved;
3. When, regardless of the preciseness of coordination, the fuse link is subjected to temporary overloads.

If close coordination is to be achieved, overloading must be avoided since it causes a significant shift in time-current characteristics.

Because of the damageability of cast-tin element fuse links (rated 140T and 200T amperes), setback allowances must be used in coordinating these fuse links as “protected” devices. These are applied by reducing the current value in the above curves by 10%. On the other hand, silver-copper eutectic element fuse links (rated 6T through 100T amperes) are nondamageable, and no such setback allowances are necessary.

The exclusive use of S&C Positrol Fuse Links—because of their inherently narrower tolerance band and because of their nondamageability—will expand the scope of coordination as follows:

1. Coordination of preferred with adjacent intermediate ratings,

giving twice as many sectionalizing points. This is true for the sequence operation of fuse links alone, or for the sequence operation of fuse links coordinated with automatic circuit reclosers.

2. Coordination of a larger number of fuse-link ratings with a given automatic circuit recloser between the fast and retarded curves.
3. Coordination through a greater range, and to higher levels of fault current, with respect to automatic circuit reclosers.
4. Coordination to higher levels of fault current with respect to sequence operation of fuse links.

The breadth of coordination described above can be obtained only by the use of S&C Positrol Fuse Links. No fuse link of low-temperature element construction (tin, lap-joint) can provide similar performance.

**NOTE**—A coordination scheme designed to take full advantage of the nondamageability and the superior coordination capabilities of S&C Positrol Fuse Links may not function satisfactorily if fuse links of the same speed but of other makes are substituted. However, S&C “T” Speed Positrol Fuse Links can replace, on a one-for-one basis, other manufacturers’ “T” speed fuse links in existing coordination schemes. Such replacements, unlike tin-element fuse links, are not subject to nuisance fuse operations (“sneakouts”) due to damage from surge currents, load cycling, vibration, and aging.

#### FUSE LINKS AVAILABLE—

| Style                   | Ampere Ratings  |
|-------------------------|-----------------|
| Universal .....         | 6T through 200T |
| Extra-Performance ..... | 6T through 200T |

